# Product Data Sheet - Step Nosing F14-170

2023 V2



# The F14-170 Step Nosing is designed to both define the step edge and help prevent slips and falls in all weather conditions.

#### COMPLIANCE

The Step Nosing is suitable for use indoors and outdoors. The anti-slip material provides all weather protection from slips and falls.

Anti-slip Properties - UL410 Standard for Slip Resistance for Floor Surface Materials AS/NZS 4586-2004 Classification: Dry: F Wet: V Ramp: R12 AS 4586-2013 Classification: P5

Salt Spray Resistance – ASTM B117: Pass Washability - ASTM D4828: Pass Rate of Burning – ASTM D635: Pass Surface Flammability - ASTM E162: Pass Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass Radioactivity - ASTM D3648: Pass

#### SUPPLY

The product is available in 100mm increments from 800mm to 1500mm. Custom lengths can also be fabricated on site from 2.45 metre and 3.06 metre lengths.

#### COMPOSITION

The F14-170 Step Nosing profile consists of 6060T5 aluminium extrusion, anodized (natural/silver colour) to 20 microns thickness.

Ecoglo N15-070 Step Edge Contrast is adhesively fixed into the extrusion. The insert is manufactured from extruded 6063T5 aluminium section. Silicon Carbide anti-slip materials are embedded in thermoset polyester carriers to integrally bond the active ingredients into the aluminium following curing at high temperature.




#### INSTALLATION

The F14-170 Step Nosing is installed with hidden fixers and can be used on a range of substrates including concrete, timber, tiles, vinyl, steel and checker plate. Uni clamp assemblies can be used for installation onto steel mesh steps.

Maximum recommended length for outdoor installation is 1500mm.

Installation is a two-step process and needs to be carried out strictly in accordance with the Ecoglo installation instructions.

Consult Installation Instructions on website for full details and surface preparation.



ecog

VISIBLY BETTER

PRODUCT CODE	PRODUCT DESCRIPTION	PRODUCT LENGTH
F14-170-800	Step Nosing 75mm x 10mm	800mm
F14-170-900	Step Nosing 75mm x 10mm	900mm
F14-170-1000	Step Nosing 75mm x 10mm	1000mm
F14-170-1100	Step Nosing 75mm x 10mm	1100mm
F14-170-1200	Step Nosing 75mm x 10mm	1200mm
F14-170-1300	Step Nosing 75mm x 10mm	1300mm
F14-170-1400	Step Nosing 75mm x 10mm	1400mm
F14-170-1500	Step Nosing 75mm x 10mm	1500mm

### Contact

## Ecoglo Fire Protection Product Trading

Address: 36-C Gloria Street, Barangay San Carlos, Binangonan Rizal 1940, Philippines Office: +632-8802-4760 Cell: +63917-514-6803 +63968-356-4773 Email: keith.phillips@ecoglo.com Web: www.ecoglo.ph www.EcogloAsia.com www.EcogloVenues.com